




94G

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	94G
Product Range	Plasterers Accessories
Product Sub-range	Multi-coat plaster beads and lath - Internal Use
Product Type	EML (diamond lath)
European Standard/ETA	BS EN13658-1:2005
DoP Ref	EXP110CPR2013

Material	Galvanized Mild Steel DX51D+Z275 to EN10346:2015
Coating/Finish/Colour	275g/m ² Zinc Coating
Length 1/Projection	2500mm
Width/Wing Length	700mm
Plaster/Render/Joist depth	13mm+ Plaster Depth
Material Gauge	0.95mm
Individual Weight (kg)	4.375
Fire Rating	Reaction to fire: Class A1
Fixing Type	Galvanised Clout Nails/Staples/Screws and Washers
Installation requirement 1	A 5-6mm gap must be provided between the lath and substrate
Installation requirement 2	Overlap sheets 50mm along short edge, and 25mm along long edge
Installation requirement 3	Fixings to perimeter at 150mm intervals, central fixings at max 350mm in a staggered formation
Installation requirement 4	Sheets should be staggered in a stretcher (brick bond) arrangement
Installation requirement 5	If overlaps are unsupported, they must be wire-tied at 150mm centres
Unit of Sale EAN	5014316400947
Sales Qty	1
Packaging weight	0
Packaged transit weight	4.375
Features/Benefits 1	Acts as a carrier for plaster where no key or backing is present
Features/Benefits 2	Can be used over chases/columns to prevent cracking
Features/Benefits 3	Can be moulded into curves/domes
Features/Benefits 4	Can easily be cut to size using tin-snips or aviation cutters
Options 1	None

HEALTH AND SAFETY INFORMATION

1. Identification

'Expamet'
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition

Galvanized Mild Steel DX51D+Z275 to EN10346:2015

3. Hazards Identification

Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures

Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures

Non-flammable material.

6. Accidental release measures

Not applicable.

7. Handling and storage

Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8. Exposure controls

Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties

Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity

Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information

High temperatures can produce fumes.

12. Ecological information

No known Hazard.

13. Disposal considerations

Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information

Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.